

TOOL SIZE		CONNECTION	MAXIMUM JARRING LOAD UP	MAXIMUM JARRING LOAD DOWN	MAXIMUM PULL/PUSH AFTER JARRING	TOTAL STROKE	PUMP OPEN AREA	MAXIMUM TORQUE	BODY JOINT TORQUE
OD	ID								
1-11/16"	9/16"	1" AMMT	10,000 lbs	10,000 lbs	42,200 lbs	13-1/4"	0.69 sq. in.	600 ft/lbs	350 ft/lbs
42.86 mm	14.28 mm		4,448 daN	4,448 daN	18,771 daN	336.55 mm	445 sq. mm	813 Nm	474 Nm
1-13/16"									
46.03 mm									
2-1/8"	3/4"	1-1/2" AMMT	18,000 lbs	18,000 lbs	103,000 lbs	12-1/2"	1.35 sq. in.	1,000 ft/lbs	700 ft/lbs
53.97 mm	19.05 mm		8,006 daN	8,006 daN	45,814 daN	317.50 mm	871 sq. mm	1,355 Nm	949 Nm
2-1/4"	3/4"	1-1/2" AMMT	22,000 lbs	22,000 lbs	103,000 lbs	12-1/2"	1.35 sq. in.	1,000 ft/lbs	700 ft/lbs
57.15 mm	19.05 mm		9,786 daN	9,786 daN	45,814 daN	317.50 mm	871 sq. mm	1,355 Nm	949 Nm
2-7/8"	1"	2-3/8" PAC	30,000 lbs	30,000 lbs	193,000 lbs	14-1/2"	2.4 sq. in.	3,200 ft/lbs	2,200 ft/lbs
73.02 mm	25.40 mm		13,344 daN	13,344 daN	85,846 daN	368.30 mm	1,548 sq. mm	4,336 Nm	2,981 Nm
3-1/8"	1-1/4"	2-3/8" REG	37,000 lbs	37,000 lbs	200,000 lbs	14-1/2"	2.94 sq. in.	5,000 ft/lbs	3,000 ft/lbs
79.37 mm	31.75 mm		16,458 daN	16,458 daN	88,960 daN	368.30 mm	1,896 sq. mm	6,775 Nm	4,065 Nm
3-1/2"									
88.90 mm									

NOTE: All specifications accurate within 15%

PATENTED